Chateau Oak



120

Sienna Oak

170

Chestnut Oak

180

Scarlett Oak

500

Alpine Oak

510

Summer Blonde

515

Willow Oak

520

Autumn Amber

550

Havana

565

Elm Oak

740

Bur Oak

Specifications and colourations are subject to manufacturing tolerances. As part of the Godfrey Hirst continuous improvement program, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

Chateau Oak

Chateau Oak has been updated with a new tri-layer oak core construction and refreshed colour palette providing a range of new timeless selections. The new construction features an 100% cross laminated oak core, utilising a whole-tree approach to engineered timber ensuring maximum stability. A 3.2mm European Oak veneer provides a luxurious oak look with true-to-life distinct knots and grain variation.

Technical Data

Type:	Timber Flooring
Total Product Thickness:	14.2mm
Units Per Box:	6 Boards Equivalent (32% Nested/Random Lengths)
m² per pallet:	114.13
Country of Origin:	Indonesia
Surface:	European Oak Veneer (3.2mm)
Backing Layer:	Ply
Coating System:	UV Cured Polyurethane

Dimensions:	1820mm x 190mm
Wear Layer:	3.2mm
m² per box:	2.075
Colours:	10
Finish:	Matte
Substrate Layer:	Cross Laminated Oak
Profile:	Micro Bevel Edge
Installation Method:	5G Insta Clic®

Performance

Moisture Content:	(EN 131831-1) 6-8% (+/-2%) at time of delivery
E3 Internal Moisture:	3.0 Watersplash - Alternative solution
Topical Moisture Resistance:	(ISO4760) No penetration through assembled join (sealing plank joints with Clicseal)
Light Reflectance Values:	100 - 32.84 | 150 - 29.84 | 500 - 23.70 | 510 - 12.83 | 520 - 12.11 | 540 - 13.80 | 550 -11.89 | 750 - 17.84 | 780 - 8.17 | 790 - 5.26
Smoke Value:	(EN ISO 9239) 11% minutes

Lipping:	(EN13489) ≤0.2mm
Suitable for Wet Areas:	Kitchen & integrated laundry - subject to proper installation and maintenance
Impact Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Flammability:	(EN ISO 9239) Loose Laid: CRF 5.1 kW/m2 | Loose Laid over Arriba 25 Underlay: CRF 3.1 kW/m2
Slip Resistance:	(AS/NZ 4586-2013) R10 / P3

Sustainability

Product Transparency:	PEFC Chain of Custody certified.
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.
Indoor Air Quality:	Green Building Council compliant for VOC emission rate limits

Micro Bevel Edge

European Oak Veneer

Premium

Matte Finish

PEFC CoC Certified

Masterspec Partner

Chateau Oak

Manufacturing Standards:
All specifications and colours are subject to manufacturing tolerances and may be changed or discontinued without notice. Product images are for reference only; actual colours may vary from samples due to printing variations, batch differences, and lighting conditions. All variations are within industry standards.

Natural Product Characteristics:
Hard flooring products may display natural variations in colour, grain, texture, and pattern between batches and individual planks or tiles. These variations are inherent characteristics of the product and do not constitute a manufacturing defect.

Water Resistant/Waterproof Flooring:
Water resistance and waterproof performance are subject to proper installation, ongoing maintenance, and compliance with local building codes and regulatory requirements.

Installation:
All hard flooring must be installed by a qualified professional in accordance with NZS AS 1884:2013, relevant referenced standards for moisture testing and subfloor preparation (e.g. AS/NZS 1080 where applicable), recognised industry best practice, and the applicable Godfrey Hirst installation instructions. Proper subfloor preparation, moisture management, and acclimatisation are essential to ensure product performance and longevity.

Maintenance:
Maintenance requirements vary by product type. Refer to the specific care and maintenance guidelines for your flooring product to ensure optimal performance and longevity.

Product-Specific Notes:
Timber: Nested/random lengths may occur. As this is a natural product, some boxes may include one 'nested' board (i.e. two boards comprising the quoted board length). All boxes will provide the coverage quoted.
Vinyl Sheet: Each colour has a specific pattern repeat and laying direction, refer to the Product Specification Sheet for details. Pay particular attention to the directional arrow to determine if the design should be installed in a standard or reverse direction. LRV indicates Light Reflectance Value, PR is Pattern Repeat, and PTS denotes Plank/Tile Size.

Warranty:
All Godfrey Hirst floors carry a comprehensive warranty supported by New Zealand after-sales service. As a New Zealand manufacturer, we recognise all consumer rights under the Consumer Guarantees Act 1993 and match any equivalent performance guarantee offered in the marketplace at the time of purchase. Commercial warranties are issued project-by-project with specific terms and conditions.

For detailed warranty information, installation guidelines, care instructions, and product characteristics, visit www.godfreyhirst.com or call 09 268 3300. For commercial project-specific warranty enquiries, contact your GH Commercial Account Manager.

Test results and certificates available on request.