Iperform 70






110
Camargue T53



130
Botticelli T82



135
Camargue T04



200
Coronet T94



320
Calais T34



350
Camargue T58



505
Camargue T83



705
Pinnacles T08



710
Elias T32




725
Pinnacles T90



748
Elias T93



750
Botticelli T93



770
Galibier T92



785
Pinnacles T98

Specifications and colourations are subject to manufacturing tolerances. As part of the Godfrey Hirst continuous improvement program, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

Iperform 70

Iperform 70

Bring performance, durability and practical style to demanding environments with Iperform 70 commercial vinyl sheet flooring from Godfrey Hirst. Designed for high-traffic spaces, its range of 14 unique designs offers versatile styling options, creating a functional foundation for commercial interiors where durability and appearance matter.

Built to withstand the demands of busy commercial environments, Iperform 70 features an impressive 0.70mm wear layer and compact, impact-resistant construction. Its durable surface is further enhanced by HyperGuard+ protective technology, providing resistance against stains and scratches to help maintain the floor's appearance over time.

Combining practical performance with easy installation, Iperform 70 is designed to meet the needs of demanding commercial spaces. Sanitec treatment helps support hygiene, while its resilient construction delivers a dependable flooring solution for high-traffic environments. With its combination of a substantial wear layer, protective surface technology and versatile design options, **Iperform 70 brings together lasting durability, easy maintenance and functional style for commercial applications.**

Technical Data

Type:	Vinyl Sheet Flooring
Wear Layer:	0.7mm
Colours:	14
Finish:	Matte
Coating System:	HyperGuard+ Performance Barrier

Total Product Thickness:	2.15mm
Roll Width:	Width: 2m, Length: 25mm
Country of Origin:	Belgium
Surface:	Embossed
Installation Method:	Direct Stick

Performance

Dimensional Stability:	(ISO 23999) 0,03% (norm ≤ 0,40%)
Impact Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Smoke Value:	Direct Stick: (EN ISO 9239) 201%.minutes

Abrasion Rating:	(EN 660-2) Group T
Light Fastness:	(EN ISO 105-B02) ≥6
Slip Resistance:	(AS 4586) P3, R10

Sustainability

Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.
Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits



Heterogenous Vinyl Sheet



Sanitec


Heavy Traffic


Strong & Durable


Water Resistant



Affordable

Iperform 70

Direct Stick

ISO 9001 Quality Management System

ISO 14001 Environment Management System

Iperform 70

All GH Commercial vinyl sheet products must be installed in accordance with relevant Australian Standards and in conjunction with the GH Commercial Vinyl Sheel Installation Instructions.

*Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.

^Subject to proper installation, maintenance and local building code/regulatory approval.