Stellar Prime





115

Polar Light



300

Radiant Comet



510

Lyra Dusk



520

Capella Star



525

Saturn Glow



545

Sunbeam Blackbutt



547

Starlight Blackbutt



555

Champagne Spotted Gum



556

Orbit Spotted Gum



560

Nova Honey



580

Asteroid Shadow



735

Meteorite Grey

Specifications and colourations are subject to manufacturing tolerances. As part of the Godfrey Hirst continuous improvement program, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

godfreyhirst.com

Stellar Prime

Bring depth, warmth and contemporary style into your home with Stellar Prime laminate flooring from Godfrey Hirst. **Designed to capture the natural character of timber**, its detailed woodgrain patterns and considered colour palette create a versatile foundation that complements a range of interior styles.

Pressed bevel edges define each plank, enhancing the overall floor design with added dimension and a more pronounced timber-inspired appearance. On selected colours, an embossed-in-register surface adds another layer of realism, with the texture following the natural grain pattern for a more authentic finish.

Designed for everyday living, Stellar Prime combines its timber-inspired aesthetic with practical performance features. Enhanced 240 Hour Water Resistance provides added confidence against everyday moisture, while the carefully considered surface detailing brings depth and definition to the floor. With its combination of pressed bevel edges, selected embossed-in-register colours and enhanced water resistance, **Stellar Prime delivers a balance of style and functionality for modern homes.**

Technical Data

Type:	Laminate Flooring
Total Product Thickness:	8mm
m² per box:	1.764
Colours:	12
Surface:	Embossed in Register on Selected Colours
Backing Layer:	Balancing Layer
Installation Method:	Uniclic®

Dimensions:	1500mm x 196mm
Units Per Box:	6 boards
m² per pallet:	105.84
Finish:	Matte
Substrate Layer:	860kg/m3 High Density Fibreboard
Profile:	Pressed Bevel

Performance

Abrasion Rating:	(EN 13329) AC4
Flammability:	(EN ISO 9239) CRF 11.0kW/m2
Warranty:	20 Year Laminate Limited Residential Warranty*

Impact Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Smoke Value:	(EN ISO 9239) 0% minutes

Sustainability

Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.
Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits


Water Resistant



Matte Finish


Uniclic® Watertight Locking System


Pressed Bevel Edge



Embossed in Register


Embossed

Stellar Prime



20 Year Laminate Limited Residential Warranty*



ISO 9001 Quality Management System



ISO 14001 Environment Management System



Celebrating Australian Species



Mid Range

Stellar Prime

All Godfrey Hirst Laminate products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Laminate Flooring Installation Instructions.
*This product comes with a residential warranty for new product installed indoors in a residential home, if properly installed and maintained. This warranty is in addition to consumers' rights under the statutory consumer guarantee provisions in the Australian Consumer Law, which may exceed the rights under this warranty. The amount recoverable under the warranty decreases after five years. For full information in respect to the scope and limitations of this warranty, please refer to the to the full terms and conditions available from your retailer, by calling 1300 444 778, or by download from www.godfreyhirst.com.
Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.