Vega

5501

Chocolate

Specifications and colourations are subject to manufacturing tolerances. As part of the Godfrey Hirst continuous improvement program, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

Vega

Durable, easy to maintain and water resistant, Vega is the perfect choice for homeowners wanting a beautiful timber look in all areas of their home. This range displays bold color variations between planks within each color selection, creating a dynamic look that's truly one-of-a-kind.

Technical Data

Type:	Vinyl Plank Flooring
Total Product Thickness:	2.5mm
Units Per Box:	16 boards
m² per pallet:	275.325
Country of Origin:	China
Surface:	Embossed in Register
Coating System:	UV Coating

Dimensions:	1227mm x 187mm
Wear Layer:	0.55mm
m² per box:	3.671
Colours:	1
Finish:	Matte
Profile:	Micro Bevel
Installation Method:	Direct Stick

Performance

Moisture Content:	(EN 13183-1) 7% (+/- 2%) at time of delivery
Classification:	(EN ISO 10874) Residential 23, Commercial 33, Industrial 42
E3 Internal Moisture:	3.0 Watersplash - Alternative solution
Topical Moisture Resistance:	(ISO4760) No penetration through assembled join
Light Reflectance Values:	5001 - 23.65 | 5101 - 28.24 | 7401 - 18.90 | 5501 - 9.67 | 3001 - 20.97 | 1001 - 42.87 | 5201 - 20.35 | 5401 - 10.11 | 7001 - 26.89 | 7501 - 19.59 | 5301 - 17.39 | 1301 - 39.26
Castor Chair:	(EN 425) No Damage

Dimensional Stability:	(EN 434) ≤ 0.10%
Abrasion Rating:	(EN 660-2) Group T
Suitable for Wet Areas:	All wet areas - subject to proper installation and maintenance
Impact Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS/NZ 4586-2013) P3, R10
Residual Indentation:	(EN 433) <0.05mm

Sustainability

Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.

Quiet Underfoot

Matte Finish

Embossed in Register

ISO 9001 Quality Management System

ISO 14001 Environment Management System

Mid Range

Vega

Colour Variation

Vega

Manufacturing Standards:
All specifications and colours are subject to manufacturing tolerances and may be changed or discontinued without notice. Product images are for reference only; actual colours may vary from samples due to printing variations, batch differences, and lighting conditions. All variations are within industry standards.

Natural Product Characteristics:
Hard flooring products may display natural variations in colour, grain, texture, and pattern between batches and individual planks or tiles. These variations are inherent characteristics of the product and do not constitute a manufacturing defect.

Water Resistant/Waterproof Flooring:
Water resistance and waterproof performance are subject to proper installation, ongoing maintenance, and compliance with local building codes and regulatory requirements.

Installation:
All hard flooring must be installed by a qualified professional in accordance with NZS AS 1884:2013, relevant referenced standards for moisture testing and subfloor preparation (e.g. AS/NZS 1080 where applicable), recognised industry best practice, and the applicable Godfrey Hirst installation instructions. Proper subfloor preparation, moisture management, and acclimatisation are essential to ensure product performance and longevity.

Maintenance:
Maintenance requirements vary by product type. Refer to the specific care and maintenance guidelines for your flooring product to ensure optimal performance and longevity.

Product-Specific Notes:
Timber: Nested/random lengths may occur. As this is a natural product, some boxes may include one 'nested' board (i.e. two boards comprising the quoted board length). All boxes will provide the coverage quoted.
Vinyl Sheet: Each colour has a specific pattern repeat and laying direction, refer to the Product Specification Sheet for details. Pay particular attention to the directional arrow to determine if the design should be installed in a standard or reverse direction. LRV indicates Light Reflectance Value, PR is Pattern Repeat, and PTS denotes Plank/Tile Size.

Warranty:
All Godfrey Hirst floors carry a comprehensive warranty supported by New Zealand after-sales service. As a New Zealand manufacturer, we recognise all consumer rights under the Consumer Guarantees Act 1993 and match any equivalent performance guarantee offered in the marketplace at the time of purchase. Commercial warranties are issued project-by-project with specific terms and conditions.

For detailed warranty information, installation guidelines, care instructions, and product characteristics, visit www.godfreyhirst.com or call 09 268 3300. For commercial project-specific warranty enquiries, contact your GH Commercial Account Manager.

Test results and certificates available on request.