


PRODUCT  
Colours



100  
PEARL

Vinyl Plank



180  
HEATHER

Vinyl Plank



300  
TOPAZ

Vinyl Plank



350  
TOTARA

Vinyl Plank



500  
ROSE GOLD

Vinyl Plank



520  
TOI TOI

Vinyl Plank




550  
TUSSOCK

Vinyl Plank



580  
SUMMIT

Vinyl Plank



700  
LIMESTONE

Vinyl Plank



720  
TITANIUM

Vinyl Plank



750  
PAUA

Vinyl Plank



780  
ONYX

Vinyl Plank



AQUILA  VINYL PLANK


Aquila is a stunning vinyl plank range that features extra wide planks in a modern Nordic inspired colour palette. Durable, easy to maintain and water resistant^ Aquila is the perfect choice to bring style to all areas of your home, including wet areas.

Product images on this flyer should only be used as a guide or point of reference. Actual samples should be inspected at your nearest retailer to confirm texture and colour before making a purchase decision. It is also noted colour appearance can vary depending upon the type of light under which a sample is viewed and light sources where the flooring is installed. ^Subject to proper installation and maintenance.

## PRODUCT

## Specifications

## AQUILA Direct Stick Plus - Vinyl Plank Product Details

Technical Data		Technical Data	
Type	Vinyl Plank	Colours	12
Plank Thickness	4.5mm	Protective Coating	Superguard®
Wear Layer	0.55mm	Finish	Matte
Dimensions	1498mm (L) x 246mm (W)	Surface	Embossed
Planks per Box	6	Profile	Micro Bevel
M <sup>2</sup> per Box	2.21m <sup>2</sup>	M <sup>2</sup> per Pallet	119.34m <sup>2</sup>
Installation Method	Direct Stick  Please refer Installation instructions for further details		



## Performance

Classification	23, 33	ISO 10582	
Dimensional Stability	Length: 0.05%	ISO 23999	
	Width: 0.05%		
	Curling: 0.00%		
Abrasion Rating	Group T	EN 660-2	
Residual Indentation	<0.1mm	ISO 24343-1	
Castor Chair	No Damage	ISO 4918	
Impact Sound Reduction	L <sub>n</sub> ,W 58	ISO 10140-3	
	IIC 51	ASTM E492-09	
	Product tested over Damtec 2.0mm Colour Underlay		
Light Fastness	≥ 6	EN ISO 105-B02	
Light Reflectiveness Values	100 Pearl 62.11%	180 Heather 17.5%	300 Topaz 27.63%
	350 Totara 22.19%	500 Rose Gold 49.53%	520 Toi Toi 34.77%
	550 Tussock 28.25%	580 Summit 30.14%	700 Limestone 21.89%
	720 Titanium 36.48%	750 Paua 20.7%	780 Onyx 26.58%
Slip Resistance	P3, R9	AS/NZ 4586	
Residential Warranty*	25 Years		
Commercial Warranty†	15 Years		
Reaction to Fire	CRF 8.6 kW/m <sup>2</sup> Smoke Value 217%.min	EN ISO 9239	
Suitable for wet areas	Yes - subject to proper installation and maintenance		
Recommended Adhesive	Refer to Godfrey Hirst Adhesive Guide <a href="http://www.godfreyhirst.com">www.godfreyhirst.com</a>		

## Sustainability

VOC Rating	Passes CETEC VOC test
Accreditation	Manufactured under a management system certified as complying with ISO 9001 & ISO14001

All product specifications and colourations are subject to nominal manufacturing tolerances. Materials supply and/or manufacturing process may be changed without notice. All Godfrey Hirst Floors Vinyl Plank products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Floors Vinyl Plank Installation Instructions.

\*These residential warranties are in addition to any rights consumers may have under Australian consumer laws. Conditions apply: For full information in respect to the scope and limitations of these warranties, this must be read in conjunction with the Godfrey Hirst Vinyl Plank Floors Care, Maintenance and Warranties guide (which also includes full information as to the installation, care and characteristics of Godfrey Hirst vinyl plank products) available from your retailer, by calling 1300 444 778, or by download from [www.godfreyhirst.com](http://www.godfreyhirst.com).

†Terms and conditions apply to all commercial warranties – contact your Godfrey Hirst account manager.

Test results and certificates are available on request.