



Apollo Hardwood



105
Blackbutt
Ivory



505
Blackbutt
Limed



525
Blackbutt
Sandbank



535
Blackbutt
Elegant



545
Blackbutt
Classic



735
Blackbutt
Stormy



520
Spotted Gum
Blonde



530
Spotted Gum
Coastal



540
Spotted Gum
Riverbank



555
Spotted Gum
Natural



710
Spotted Gum
Ash



790
Spotted Gum
Burnt

While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference. Actual samples should be inspected at your nearest retailer to confirm texture and colour before making a purchase decision. *Subject to proper installation and maintenance.

Apollo Hardwood

Comprising of homegrown wood species Blackbutt and Spotted Gum in a stunning longboard, Apollo Hardwood promises a distinctly Australian look. Each design is represented in six distinct shades to complement your unique interior style. With the astonishing durability and waterproof[^] properties of Godfrey Hirst hybrid flooring, Apollo Hardwood is ideal for all areas of a busy home.

Technical Data

Type	Hybrid	Finish	Matte
Plank Thickness	6.5mm	Surface	Embossed
Wear Layer	0.5mm	Top Layer	Decorative Film & Wear Layer
Dimensions	1830mm (L) x 152mm (W)	Substrate Layer	Trigon [®] Core Technology (Limestone Composite)
Planks per Box	6	Backing Layer	1.5mm EVA
M² per Box	1.67m ²	Profile	Micro Bevel
M² per Pallet	110.22m ²	Protective Coating	PUR
Colours	12		
Installation Method	Unipush™ Tap fold-down		

Performance

Dimensional Stability	Length: 0.05% Width: -0.00% Curling: 0.00%	ISO23999
Thermal Resistance	0.056m ² .K/w	EN 12667
Thermal Conductivity	0.115 W/(m.K)	EN 12667
Abrasion Rating	Group T	EN 660-2
Swelling After Submersion in Water	0.3%	ISO 24336
Impact Sound Reduction	Test Application	Ln'T,w Result
	150mm Slab + 28mm Furrings + 10mm Plasterboard	50
	200m Slab	54
	200mm Slab + 28mm Furrings + 10mm Plasterboard	49
	200mm Slab + R2.5 Insulation + 100mm Cavity + 10mm Plasterboard	46
	250mm Slab + 28mm Furrings + 10mm Plasterboard	48
Light Fastness	Grade 6	EN ISO 105-B02
Fire Classification	CRF 10.9kW/m ² Smoke Value 81% minutes	ISO 9239
Slip Resistance	P3	AS/NZ 4586 - 2013
Residential Warranty*	25 Year Hybrid Limited Residential Warranty	
Commercial Warranty†	15 Year Commercial Warranty available upon request	

Sustainability

Indoor Air Quality	Green Building Council compliant for VOC emission rate limits
---------------------------	---



Manufactured under a quality and environmental system certified as complying with ISO9001 and 14001. Test results and certificates are available on request. Specifications and colourations are subject to manufacturing tolerances. As part of Godfrey Hirst's continuous improvement process, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. All Godfrey Hirst hybrid floors must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Hybrid Floors Installation Instructions. *These residential warranties are in addition to consumers' rights under the statutory consumer guarantee provisions in the Australian Consumer Law, which may exceed the rights under these warranties. Conditions apply: Warranties apply to residential indoor use of the floor installed and maintained in accordance with Godfrey Hirst's guidelines. The amount recoverable under the warranties decreases after five years. For full information in respect to the scope and limitations of these warranties, refer to the Godfrey Hirst Hybrid Floors Care, Maintenance and Warranties guide (which also includes full information as to the installation, care and characteristics of Godfrey Hirst hybrid products) available from your retailer, by calling 1300 444 778, or by download from www.godfreyhirst.com †Terms and conditions apply to all commercial warranties – contact your Godfrey Hirst account manager.