

PRODUCT
Colours



180
COFFEE
OAK

High Feature
Grade



300
NATURAL
OAK

Select Grade



510
COASTAL
OAK

Medium Feature
Standard Grade



530
CINNAMON
OAK

Medium Feature
Standard Grade



560
WEATHERED
OAK

Select Grade



710
ASHEN
OAK

High Feature
Grade



OAK ELEGANCE

With a real timber surface, Oak Elegance provides a unique look for your home with distinct knots and grain variation. The Oak Elegance boards come in various grades which are indicative of the overall character that your finished floors will have. Choose a High Feature Grade for a rustic look, Select Grade for limited variation or Medium Feature Standard Grade for something in between. The six standard width colours are also available in a 2200 x 220mm wide board option.

Every timber floor is different, and will always vary from any images or samples with colour, grain and textural variation. The illustrated patterns and colours/samples are only an image/example and not a full overview of all the different nuances within the natural unique design of a timber floor. Colour appearance can also vary depending upon the type of light under which an image/sample is viewed and light sources where the flooring is installed. For a representative view of the surface structure and variation of a board take a look at the large samples and ask your Godfrey Hirst account manager.

PRODUCT

Specifications

OAK ELEGANCE - Timber Product Details



Technical Data

Type	Engineered Timber
Plank Thickness	14mm
Wear Layer	3mm
Dimensions	1900mm (L) x 190mm (W)
Planks per Box	8 Boards Equivalent [^] (Nested / Random lengths may occur)
M ² per Box	2.888m ²
M ² per Pallet	115.52m ²
Colours	6
Finish	Matte
Surface	Brushed and Real Timber Surface
Profile	Micro Bevel Edge
Substrate Layer	Poplar
Backing Layer	Ply
Installation Method	Drop Lock. Please refer Godfrey Hirst Timber Installation Instructions for further details.

Performance

Coating System	UV Lacquer	
Impact Sound Reduction	Ln,W 56 IIC 55	ISO 10140-3 ASTM E492-09
Moisture Content	6-8% (+/- 2%) at time of delivery	EN 13183-1
Reaction to Fire	CRF 2.2kW/m ² (over underlay) Smoke Value 108%.min	AS/ISO 9239
Slip Resistance	P3	AS/NZ 4586 - 2013
Warranty*	25 Year Residential Structural Warranty 15 Year Residential Finish Warranty	
Commercial Warranty [†]	Available on Request	

Sustainability

VOC Rating	CETEC Compliant for VOC Emission Rate Limits
------------	--

Test results and certificates are available on request.

All product specifications and colourations are subject to nominal manufacturing tolerances. Materials supply and/or manufacturing process may be changed without notice. All Godfrey Hirst engineered timber floors must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Timber Floors Installation Instructions.

*These residential warranties are in addition to any rights consumers may have under Australian consumer laws. Conditions apply: For full information in respect to the scope and limitations of these warranties, this must be read in conjunction with the Godfrey Hirst Timber Floors Care, Maintenance and Warranties guide (which also includes full information as to the installation, care and characteristics of Godfrey Hirst Timber products) available from your retailer, by calling 1300 444 778, or by download from www.godfreyhirst.com.

[†]Terms and conditions apply to all commercial warranties – contact your Godfrey Hirst Floors commercial account manager.

[^]Nested/Random lengths may occur. As this is a natural product, some boxes may include one 'nested' board. (i.e. two boards comprising of the quoted board length). All boxes will provide the coverage quoted.