



Pioneer Brushed



545
Blackbutt



555
Spotted Gum

While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference. Actual samples should be inspected at your nearest retailer to confirm texture and colour before making a purchase decision.

Pioneer Brushed

Pioneer is a stunning timber floor available in popular Australian species – Blackbutt and Spotted Gum – with a variety of size and finish options. Choose your preferred style and width, and consider mixing board lengths for beautiful natural Australian style flooring.

The brushed finish adds texture to the surface for natural rustic charm. Also available in a satin option for a traditional smooth, polished finish.

Technical Data

Type	Engineered Timber			
Board Thickness	14mm			
Wear Layer	3mm			
Dimensions	1820mm (L) x 130mm (W)	1820mm (L) x 180mm (W)	2100mm (L) x 130mm (W)	2100mm (L) x 180mm (W)
Boards per Box	8 boards equivalent [^]	6 boards equivalent [^]	8 boards equivalent [^]	6 boards equivalent [^]
M² per Box	1.89m ²	1.97m ²	2.18m ²	2.27m ²
M² per Pallet	90.85m ²	98.28m ²	104.83m ²	113.4m ²
Colours	2			
Installation Method	Insta Clic [®]	Please refer Godfrey Hirst Timber Installation Instructions for further details.		
Finish	Matte			
Surface	Brushed, 7-coat UV Lacquer			
Substrate Layer	Multiply			
Profile	Square Edge			

Performance

Abrasion Rating	>=500r	ASTM D 4060-CS 17		
Moisture Content	8-10%	EN 131831-1		
Impact Sound Reduction	Test Application	Ln'T,w Result Underlay: 2.0mm IXPE	Ln'T,w Result Underlay: 2mm rubber	
	150mm Slab + 28mm Furrings + 10mm Plasterboard	53	55	ISO140-7 / ISO717.2
	200m Slab	57	59	
	200mm Slab + 28mm Furrings + 10mm Plasterboard	52	54	
	200mm Slab + R2.5 Insulation + 100mm Cavity + 10mm Plasterboard	49	51	
	250mm Slab + 28mm Furrings + 10mm Plasterboard	51	53	
Reaction to Fire	CRF 3.2 kW/m ² Smoke Value 74% min	AS/ISO 9239		
Slip Resistance	P3	AS 4586		
Residential Warranty*	25 Year Structural 15 Year Finish			
Commercial Warranty[†]	Available on Request			

Sustainability

Indoor Air Quality Green Building Council compliant for VOC emission rate limits



^{*}Nested/Random lengths may occur. As this is a natural product, some boxes may include one 'nested' board (i.e. two boards comprising of the quoted board length). All boxes will provide the coverage quoted. Manufactured under a quality and environmental system certified as complying with ISO9001 and 14001. Test results and certificates are available on request. Specifications and colourations are subject to manufacturing tolerances. As part of Godfrey Hirst's continuous improvement process, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. All Godfrey Hirst timber floors must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Timber Floors Installation Instructions. ^{*}These residential warranties are in addition to consumers' rights under the statutory consumer guarantee provisions in the Australian Consumer Law, which may exceed the rights under these warranties. Conditions apply: Warranties apply to residential indoor use of the floor installed and maintained in accordance with Godfrey Hirst's guidelines. The amount recoverable under the warranties decreases after five years. For full information in respect to the scope and limitations of these warranties, refer to the Godfrey Hirst Timber Floors Care, Maintenance and Warranties guide (which also includes full information as to the installation, care and characteristics of Godfrey Hirst timber floors) available from your retailer, by calling 1300 444 778, or by download from www.godfreyhirst.com