



# Pioneer Satin



545  
**Blackbutt**



555  
**Spotted Gum**

While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference. Actual samples should be inspected at your nearest retailer to confirm texture and colour before making a purchase decision.

# Pioneer Satin

Pioneer is a stunning timber floor available in popular Australian species – Blackbutt and Spotted Gum – with a variety of size and finish options. Choose your preferred style and width, and consider mixing board lengths for beautiful natural Australian style flooring.

The satin option for a traditional smooth, polished finish. Also available in a brushed finish that adds texture to the surface for natural rustic charm.

## Technical Data

Type	Engineered Timber	
Board Thickness	14mm	
Wear Layer	3mm	
Dimensions	1820mm (L) x 136mm (W)	2100mm (L) x 136mm (W)
Boards per Box	8 boards equivalent <sup>^</sup>	8 boards equivalent <sup>^</sup>
M <sup>2</sup> per Box	1.98m <sup>2</sup>	2.28m <sup>2</sup>
M <sup>2</sup> per Pallet	95.04m <sup>2</sup>	109.67m <sup>2</sup>
Colours	2	
Installation Method	Insta Clic <sup>®</sup>	Please refer Godfrey Hirst Timber Installation Instructions for further details.
Finish	Matte	
Surface	Satin, 7-coat UV cured lacquer	
Substrate Layer	Multiply	
Profile	Square Edge	

## Performance

Abrasion Rating	>=500r	ASTM D 4060-CS 17	
Moisture Content	8-10%	EN 131831-1	
Impact Sound Reduction	<b>Test Application</b>	<b>Ln'T,w Result</b>	<b>Ln'T,w Result</b>
		<b>Underlay: 2.0mm IXPE</b>	<b>Underlay: 2mm rubber</b>
	150mm Slab + 28mm Furrings + 10mm Plasterboard	53	55
	200m Slab	57	59
	200mm Slab + 28mm Furrings + 10mm Plasterboard	52	54
	200mm Slab + R2.5 Insulation + 100mm Cavity + 10mm Plasterboard	49	51
	250mm Slab + 28mm Furrings + 10mm Plasterboard	51	53
Reaction to Fire	CRF 3.2 kW/m <sup>2</sup>	EN ISO 9239	
	Smoke Value 74%.min		
Slip Resistance	P2	AS 4586	
Residential Warranty*	25 Year Structural 15 Year Finish		
Commercial Warranty†	Available on Request		

## Sustainability

Indoor Air Quality	Green Building Council compliant for VOC emission rate limits
--------------------	---



<sup>^</sup>Nested/Random lengths may occur. As this is a natural product, some boxes may include one 'nested' board (i.e. two boards comprising of the quoted board length). All boxes will provide the coverage quoted. Manufactured under a quality and environmental system certified as complying with ISO9001 and 14001. Test results and certificates are available on request. Specifications and colourations are subject to manufacturing tolerances. As part of Godfrey Hirst's continuous improvement process, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. All Godfrey Hirst timber floors must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Timber Floors Installation Instructions. \*These residential warranties are in addition to consumers' rights under the statutory consumer guarantee provisions in the Australian Consumer Law, which may exceed the rights under these warranties. Conditions apply: Warranties apply to residential indoor use of the floor installed and maintained in accordance with Godfrey Hirst's guidelines. The amount recoverable under the warranties decreases after five years. For full information in respect to the scope and limitations of these warranties, refer to the Godfrey Hirst Timber Floors Care, Maintenance and Warranties guide (which also includes full information as to the installation, care and characteristics of Godfrey Hirst timber floors) available from your retailer, by calling 1300 444 778, or by download from [www.godfreyhirst.com](http://www.godfreyhirst.com)