

ROYAL OAK TWIST

| | |
|---------------------------------------|---|
| Product Name | Royal Oak Twist |
| Product Number | 094541 |
| Description | Cut Pile |
| Construction | Tufted |
| Width | 3.66 metres (12ft. Broadloom) |
| Pile Content | 100% Solution Dyed Nylon (Soft Handle) |
| ACCS Grading | Residential Extra Heavy Duty (Including Stairs), 6 Star, Reg No: 15136 |
| ACCS ECS Grading | Level 4, Reg No: 15136 |
| Yarn Specification | BCF (Bulk Continuous Filament) |
| Insect Resistance | N/A |
| Gauge | 1/10 th (39.4/10cm) |
| Pile Height / Carpet Thickness | 16.0mm / 19.0mm + / - 1.0mm |
| Pile Weight | 2034gms/m ² (60oz/yd ²) + / - 5% |
| Primary Backing | Woven Polypropylene |
| Secondary Backing | Softbac |
| Backing Adhesive | SBR Latex |
| Bond Strength | 30 kgf / 50mm (30 Newtons) |
| Tuft Withdrawal | 10 kgf (10 Newtons) |
| Pattern Repeat | N/A |
| Treatments | Stain Protection |
| Colour Variation | Colour may vary from dye lot to dye lot. |
| Static Control | For installations that require additional static control Godfrey Hirst NZ carpet can be treated during manufacturing. |
| Material Variation | Backing or raw material may change without notice, depending on raw material availability. |
| Product Variation | Variable weights and / or colours can be produced to meet Individual requirements. For further details contact your local Godfrey Hirst Representative. |

SHIFT LINES: Construction of this carpet may involve the occurrence of shift lines across the width of the carpet. Certain light sources shining across the carpet may accentuate the lines in the form of shadowing. This is not a manufacturing fault and will not affect the carpets wear or durability.

SHADING IN CUT-PILE CARPET: Shading (permanent pile reversal) refers to the phenomena where some areas of carpet appear lighter or darker than others. Cut-pile carpets have a propensity for shading. Despite extensive research the exact factors which cause shading are not fully understood. It is known that

shading does not effect the wear or durability of carpet and is not a manufacturing fault or flaw. When selecting a carpet remember that shading is a feature of cut-pile carpet.

LAYING: It is recommended that this carpet be laid in accordance with AS/NZ 2455.1.2007 unless otherwise specified.

COLOUR VARIATION: Colour reproduction to sample may vary to normal dye lot variation.