

PRODUCT

Swatches

0100
ICE WHITELuxury
Vinyl Plank0180
RUGGED
EARTHLuxury
Vinyl Plank0300
COASTAL
BLONDELuxury
Vinyl Plank0350
SOUTHERN
HUELuxury
Vinyl Plank0510
PUMICELuxury
Vinyl Plank0520
NATURAL
STONELuxury
Vinyl Plank0700
STORMY
GREYLuxury
Vinyl Plank0790
IRON SANDSLuxury
Vinyl Plank

ALPINE LUXURY VINYL PLANK


With an exceptionally realistic timber look, the Alpine range of luxury vinyl plank provides a flexible, durable and water resistant floor suitable for residential interiors. Performance Classification 23/31.

The Alpine **DS** direct stick option is great for installations in wet areas as it can be glued directly to a variety of subfloors, including concrete.

PRODUCT

Specifications

ALPINE - Vinyl Plank Product Details

Technical Data		Technical Data	
Type	Luxury Vinyl Plank	Colours	8
Plank Thickness	2.0mm	Protective Coating	UV Coating
Wear Layer	0.3mm	Finish	Matte
Dimensions	1227mm (l) x 187mm (w)	Surface	Regular Embossing
Planks per Box	16	Profile	Square Edge
M ² per Box	3.671m ²	M ² per Pallet	330.392m ²
Installation Method	Direct Stick  Please refer Installation instructions for further details		

Performance

Classification	Heterogeneous Vinyl Flooring Residential 23, Commercial 31	
Dimensional Stability	≤ 0.10%	EN 434
Abrasion Rating	Group T	EN 660-2
Residual Indentation	< 0.03mm	EN 433
Furniture Leg	No Damage	EN 424
Castor Chair	No Damage	EN 425
Thermal Performance	0.040 (m ² K) /W	EN 12667
Light Fastness	≤ 6	EN ISO 105-B02
Chemical Resistance	Good Resistance	EN 423
Electrical Propensity	Pass	EN 1815
Reaction to Fire	> 9.2kW/m ² < 70% .min Bfl-S1	AS ISO 9239-1 EN 13501-1
Slip Resistance	R10 / P2	AS 4586-2013
Warranty [†]	Available on Request	
Recommended Adhesive	Polymer 265 Adhesive - General application Polymer 8001 - High heat exposure and wet area application	

Sustainability

VOC Rating	Floorscore, CETEC & E1 compliant for VOC emission rate limits
Accreditation	Manufactured under a management system certified as complying with ISO9001 & ISO14001

All product specifications and colourations are subject to nominal manufacturing tolerances. Materials supply and/or manufacturing process may be changed without notice. All Godfrey Hirst Floors Vinyl Plank products must be installed in accordance with relevant New Zealand Standards and in conjunction with the Godfrey Hirst Floors Vinyl Plank Installation Instructions.

[†]Warranty terms and conditions apply.

Test results and certificates are available on request.

