



Apollo XL

Hybrid



100
Snow



170
Delaware



515
Pyrenees




525
Alpine Gum



540
Natural Fumed Oak




545
Blackbutt



550
Aged Fumed Oak



555
Spotted Gum



570
Wellington



720
Reclaimed Oak



730
Boston



790
Midnight

Product images on this flyer should only be used as a guide or point of reference. Actual samples should be inspected at your nearest retailer to confirm texture and colour before making a purchase decision. It is also noted colour appearance can vary depending upon the type of light under which a sample is viewed and light sources where the flooring is installed. Please note some colours in this range (as noted above and on front of samples) have a visual design effect that results in tonal variations amid the boards for a natural timber look. Please seek to view larger samples and consult with your retailer for further advice. ^Subject to proper installation and maintenance.

Apollo XL

Hybrid

Apollo XL is a stunning hybrid floor that is extremely hard wearing, stable and waterproof*, making it perfect for use in all areas of your home. With micro bevel edges and an embossed matte finish, Apollo XL authentically replicates a natural timber wood grain look. A scratch and stain resistance surface coating means Apollo XL can easily withstand the everyday wear and tear of busy family homes.

Technical Data

Type	Hybrid	Finish	Matte
Plank Thickness	6.5mm	Surface	Embossed
Wear Layer	0.5mm	Top Layer	Decorative Film & Wear Layer
Dimensions	1500mm (L) x 180mm (W)	Substrate Layer	Trigon® Core Technology (Limestone Composite)
Planks per Box	6	Backing Layer	1.5mm EVA
M ² per Box	1.62m ²	Profile	Micro Bevel
M ² per Pallet	113.40m ²	Protective Coating	PUR & Scratch Resistance
Colours	12		
Installation Method	UNIPUSH®		

Performance

Dimensional Stability	Length: 0.05% Width: -0.00% Curling: 0.00%	ISO 23999
Thermal Resistance	0.056m ² .K/W	EN 12667
Thermal Conductivity	0.115 W/(m.K)	EN 12667
Abrasion Rating	Group T	EN 660-2
Swelling After Submersion in Water	0.3%	ISO 24336
Impact Sound Reduction	Ln,W 52 IIC 58	ISO 10140-3 ASTM E492-09
Light Fastness	Grade 6	ISO 105-B02
Fire Classification	CRF 10.9kW/m ² Smoke Value 81% minutes	EN ISO 9239
Slip Resistance	P3	AS/NZ 4586
Warranty	Available on request	

Sustainability

VOC Rating	Passes CETEC VOC Test
------------	-----------------------



All product specifications and colourations are subject to nominal manufacturing tolerances. Materials supply and/or manufacturing process may be changed without notice. All Godfrey Hirst Floors Vinyl Plank products must be installed in accordance with relevant New Zealand Standards and in conjunction with the Godfrey Hirst Floors Vinyl Plank Installation Instructions.
†Warranty terms and conditions apply. Test results and certificates are available on request.