



### How to order

For samples and sales, contact your local sales office or visit our website

[www.feltex.com](http://www.feltex.com)  
[www.feltex.co.nz](http://www.feltex.co.nz)

### Head Office

**Melbourne**  
 T 1300 130 239  
 F 1800 654 595  
[feedback@feltex.com](mailto:feedback@feltex.com)

### Sales Offices

**Melbourne**  
 2 Gilbertson Road  
 Laverton North VIC 3026  
 T +61 3 9368 8100

**Sydney**  
 28 Percival Road  
 Smithfield NSW 2164  
 T +61 2 8784 8700

**Brisbane**  
 33 Gassman Drive  
 Smithfield NSW 2164  
 T +61 7 8784 8700

**Perth**  
 1/5 Leeway Court  
 Osborne Park WA 6017  
 T +61 8 9242 7643

**Adelaide**  
 Unit 12, 60-66 Richmond Rd  
 Keswick SA 5035  
 T +61 409 938 096

### International Offices

**New Zealand**  
 52 Ash Road, Wiri  
 Manukau City 2104  
 Auckland, New Zealand  
 T (freephone) 0800 100 008  
[www.feltex.co.nz](http://www.feltex.co.nz)

**Singapore**  
 200 Jalan Sultan  
 #07-310 Textile Centre  
 Singapore 199018

### Technical Specifications

Description	Textured loop pile
Fibre content	100% BCF nylon
Pile weight	745g/m <sup>2</sup>   22oz/yd <sup>2</sup>
Machine gauge	47.2/10cm   1/12th
Pile height	4.0mm +/- 1mm
Backing structure	MediShield™ impervious backing
Width	1.95 metres
Country of origin	Australia
Minimum order	40m <sup>2</sup>

### Performance

Flammability	Result - mean 7.3kw/m <sup>2</sup> (direct stick) <sup>†</sup>   Smoke Value 189% min (direct stick) <sup>†</sup> Suitable for patient care areas 9a and 9c
Stain treatment	Stainguard®
Biocontaminant control	Bioshield® - anti-microbial treatment
ACCS	Registration: Label # 13061   Grading: Contract Extra Heavy Duty and Stairs <sup>†</sup>
Light reflection values	Results available on request
Warranty	15 year*
Antistatic	Permanent conductive fibre <3.5kv at 21° and 20% RH
Push/pull forces	Independently tested for push pull forces, all under maximum recommendation (Snook and Ciriello report, 1991)
Tolerances	As per AS1385 or +/- 5% (whichever is greater)

### Sustainability

PVC minimisation	100% PVC free
Recycled content	Minimum of 60% recycled content in the backing structure Average of 40% recycled content by weight of product
Indoor air quality	Green Building Council and Green Label Plus compliant for VOC emission rate limits <sup>†</sup>
Product stewardship	100% recyclable within Australia using a TQSCI certified post consumer recycling program
Accreditation	Carpet Institute of Australia (CIAL) Environmental Classification Scheme (ECS) Level 4 <sup>†</sup> Member of the Green Building Council of Australia Manufactured under a certified Quality Management System ISO9001 Manufactured under a certified Environmental Management System ISO14001

Specifications are subject to manufacturing variances. As part of Feltex Carpets' continuous improvement program, Feltex Carpets reserves the right to change the specifications of or delete colours of this product without notice. All Feltex carpets must be installed in accordance with AS2455 (Parts 1 & 2) and the Feltex Carpets Installation Instructions. \*Terms and conditions apply. <sup>†</sup>Test results are available on request. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

### Features & Benefits:

- An impervious moisture barrier
- Biocontaminate control
- Excellent colourfast properties
- BCA compliance
- 100% PVC & BPA free
- Rolling resistance  
(complies with Snook and Ciriello push/pull requirements)
- Excellent soil concealing abilities
- Superior appearance retention
- Sound and glare reduction

Meets Green Label Plus Specifications



Manufactured under an environmental, quality and health and safety system certified and complying with ISO14001, ISO9001 and AS4801 by accredited certification bodies.