

Head Office

7 Factories Road
 South Geelong 3220
 Victoria Australia
 Email: gfirst@godfreyhirst.com
 www.godfreyhirst.com

Postal Address

PO Box 93
 Geelong 3220
 Victoria Australia
 Telephone: +61 (3) 5225 0222
 Facsimile: +61 (3) 5222 3885

PRODUCT	:	HEALTHCARE CARPET	
PRODUCT/PATTERN NAME	:	PEARL	
<hr/>			
DESCRIPTION	:	Patterned Modulated Loop Pile	
DESIGN	:	Subtle multicolour	
YARN CONSTRUCTION	:	100% BCF Nylon	
TOTAL PILE WEIGHT	:	745 gms/m ² - 22 oz/yd ² (Tolerance ±5%)	
PILE HEIGHT	:	4 mm (Tolerance ± 1mm)	
MACHINE GAUGE	:	47.2 per 100 mm [1/12 th Gauge]	
PRIMARY BACKING	:	Synthetic	
SECONDARY BACKING	:	Healthbac™ - Impervious moisture barrier	
WIDTH	:	1.95 metres wide [minimum]	
ACCS GRADING	:	Contract Extra Heavy Duty & Stairs	
ENVIRONMENTAL CERTIFICATION	:	ECS - Level 4	
ANTISTATIC	:	Permanent Conductive Fibre < 3.5KV at 21°C and 20% RH.	
PUSH/PULL FORCES	:	The construction of our Healthcare carpets have been independently tested for push/pull forces to ensure the force measurements are under the maximum recommendations published in the Snook and Ciriello (1991) report.	
ANTIMICROBIAL	:	This carpet is treated with BIOSHIELD to inhibit the growth of E-coli, Staphylococcus Aureus and other odour causing bacteria	
INDOOR AIR QUALITY	:	Total Volatile Organic Compounds (TVOC's) Emission level test results for this product complies with Green Label Plus criteria and CIA's - ECS requirements.	
RADIANT HEAT SOURCE	:	CHF Value 7.3 kw/m ²	
AS ISO 9239.1.2003	:	Smoke Value 189 % min Suitable for Patient Care Areas 9a and 9c	
STAIN PROTECTION	:	StainWarden™	
RESISTANCE TO INSECT PESTS		TUFT WITHDRAWAL FORCE	
A.S. 2001.6.1:	Pass	A.S. 2111.15:	30 Newton (minimum)
COLOURFASTNESS TO SOLVENTS		COLOUR FASTNESS TO LIGHT	
A.S. 2001.4.16:	4-5	B.S. 1006.B02:	6 min
COLOUR FASTNESS TO SHAMPOO		COLOUR FASTNESS TO RUBBING	
A.S. 2111.19.2:	4-5	A.S. 2111.19.1:	4-5 min
COLOUR FASTNESS TO BLEACHING		COLOURFASTNESS TO WATER	
A.S. 2001.4.11:	4-5	A.S. 2001.4.11:	4-5 min
EXTRACTABLE MATTER			
Dichloromethane Extract			
A.S. 2001.3.4:			1.0% Maximum
INSTALLATION REQUIREMENTS	:	as per Godfrey Hirst Carpets Installation recommendations	